

3M™ Particulate Filter 5935, P2/P3*



Description

3M™ Particulate Filter 5935 is one of the 3M™ 5000 series particulate filters. These are used with 3M™ Half and Full Face respirators.

Features

- Lightweight and provides low breathing resistance
- Low profile and well balanced twin filter design
- Suitable for use with 3M™ Half Face Respirators 6000/7500 Series and 3M™ Full Face Respirators 6000/7000 Series

Specifications

- Filter Rating: P2/P3*
- Provides protection against certain mechanically and/or thermally generated particulates.
- For use with the 3M™ Filter Retainer 501 on the 3M™ 6000 Series Cartridges (see figure below)
- Note: Higher P3 protection only achieved with a 3M Full Face Respirator. Otherwise P2 protection level when worn on a 3M Half Face Respirator
- Weight: 3 gm per filter (nominal)
- Note: The 5935 filters are available in Australia only

Hazards/Tasks

- For protection against certain dusts, mists and fumes such as sanding, grinding, cutting, drilling metal, masonry, wood and concrete.
- Also for protection against certain
- highly toxic particulates when worn on 3M approved full face respirator e.g. Beryllium (ref AS/NZS 1715)

Standards

- Complies with AS/NZS 1716 (Respiratory protective devices).
- Use in accordance with AS/NZS 1715 (Selection, use and maintenance of respiratory protective equipment).

When to change particulate filters

The service life of a particulate filter is indicated by a change in breathing resistance. As the filter continues to capture contaminants, the ease of breathing will reduce. Deciding when to change to out the filter is therefore based on the wearers' individual assessment of breathing resistance and comfort.



* Higher P3 protection only achieved when worn with a 3M Full Face Respirator. Otherwise P2 protection level when worn on a 3M Half Face Respirator.

Technical Specifications

When selected and used in accordance with the standard (AS/NZS 1715) and for the contaminants specified, this filter is capable of providing the following protection:

- With a 3M 6000/7500 Series Half Face Respirator: Particles - for airborne concentrations up to 10 times the Workplace Exposure Standard (WES).
- With a 3M 6000/7800 Series Full Face Respirator: Particles - for airborne concentrations up to 100 x WES

Warning and Limitations

Particular attention should be given to warning statements where indicated. Proper selection, fit, training, use and appropriate maintenance are essential in order for the product to help protect the wearer from certain airborne contaminants. Failure to follow all instructions on the use of these respiratory protection products and/or failure to properly wear the complete product during all periods of exposure may adversely affect the wearer's health, lead to severe or life threatening illness or permanent disability.

Always be sure that the complete product is:

- Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure;
- Replaced when necessary.

For suitability and proper use follow local regulations, refer to all information supplied or contact an occupational hygienist, safety professional or 3M representative on the Tech Assist Helpline - Australia 1800 024 464 or New Zealand 0800 364 357.

Use this respirator system strictly in accordance with all User Instructions:

- Do not submerge the filters in liquid.
- Do not use in atmospheres containing less than 19.5% oxygen. (3M definition. Individual countries may apply their

own limits on oxygen deficiency. Seek advice if in doubt).

- Do not use these products in pure oxygen or oxygen enriched atmospheres.
- Do not use for respiratory protection against atmospheric contaminants and concentrations which have poor warning properties or are unknown or immediately dangerous to life and health (IDLH) or against contaminants/concentrations which generate high heats of reaction with chemical filters.
- Do not use in airborne concentrations above those specified in **Technical Specifications**.
- Leave the contaminated area immediately if:
 - Any part of the system becomes damaged.
 - Airflow to the face piece decreases or stops.
 - Breathing becomes difficult or increased breathing resistance occurs.
 - Dizziness or other distress occurs.
 - You smell or taste contaminants or irritation occurs.
- Never alter, modify or repair this device.
- These products do not contain components made from natural rubber latex.

NOTE: Save all user instructions for continuing reference.

Shelf Life, Storage and Transportation

Shelf life of the unopened product is five (5) years from date of manufacture when stored in temperature range -10°C to 50°C and at less than 90% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Storing the filters (with the respirator) in an airtight container, will reduce exposure to the work environment and help prolong the life of the equipment.

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the product for its intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



Personal Safety Division

3M Australia Pty Ltd
Building A, 1 Rivett Rd
North Ryde NSW 2113
TechAssist Helpline: 1800 024 464
E-mail: techassist@mmm.com.au
Website: www.3M.com/au/PPEsafety

3M New Zealand Ltd
94 Apollo Drive
Rosedale, Auckland 0632
Tech Helpline: 0800 364 357
Customer services: 0800 252 627
Website: www.3M.com/nz/PPEsafety